

CLAIRMONT LENS LIST - TECHNICAL SPECIFICATIONS

35MM FORMAT LENSES

35MM ZOOM LENSES

<u>ANGENIEUX OPTIMO</u>	<u>T-STOP</u>	<u>MIN. FOCUS</u>	<u>MOUNTS</u>	<u>WT/LBS</u>	<u>LENGTH</u>	<u>FRONT DIA.</u>
15-40MM ANG. OPTIMO	T2.6/22	2'	PL	4 lbs	7 1/2"	114MM
17-80MM ANG. OPTIMO	T2.2/22	2'	PL	11 lbs	13"	136MM
28-76MM ANG. OPTIMO	T2.6/22	2'	PL	4.5 lbs	7 1/2"	114MM
24-290MM ANG. OPTIMO	T2.8/22	4'	PL	24.5 lbs	18"	162MM

35MM ZOOM LENSES

	<u>T-STOP</u>	<u>MIN. FOCUS</u>	<u>MOUNTS</u>	<u>WT/LBS</u>	<u>LENGTH</u>	<u>FRONT DIA.</u>
15-300MM ANG.	T5/22	5'	PL	5 lbs	8 1/5"	98.40MM
17-102MM ANG.	T2.9/22	2'6"	PL-BNCR	19 lbs	16 1/4"	155MM
20-120MM ANG.	T2.9/22	3'6"	PL-BNCR	11 lbs	12 1/2"	124MM
25-250MM ANG.	T3.9/22	5'6"	PL-BNCR	6.5 lbs	10 1/2"	110.50MM
25-250MM ANG. HR	T3.5/22	5'7"	PL-BNCR	10.5 lbs	12 3/4"	133MM
14-70MM COOKE	T3.1/22	2'4"	PL-BNCR	16 lbs	15 3/4"	197MM
18-100MM COOKE	T3/22	2'4"	PL-BNCR	13.75 lbs	13 1/2"	149MM
20-60MM COOKE	T3.1/22	2'4"	PL-BNCR	7 lbs	9 3/4"	120MM
20-100MM COOKE	T3.1/22	2'4"	PL-BNCR	11.5 lbs	13 1/2"	142MM
25-250MM COOKE MK2	T4/22	5'6"	PL-BNCR	11.5 lbs	12 5/8"	120MM
25-250MM COOKE MK3	T3.7/22	5'6"	PL-BNCR	18 lbs	15"	152MM
17-35MM CENTURY	T3.1/22	1'6"	PL	2.5 lbs	4 1/4"	95MM
23-460MM CENTURY	T8/32	5'	PL-BNCR	7.5 lbs	10"	120MM
28-70MM CENTURY	T3/22	3'	PL	3 lbs	5"	95MM
18-90MM TECHNO	T2.3/22	2'6"	PL-BNCR	12.5 lbs	13 3/4"	142MM
18.5-55MM TECHNO	T2.4/22	2'4"	PL-BNCR	8 lbs	9 1/4"	120MM
25-80MM OPTAR	T3.3/22	3'	PL	2 lbs	9 1/4"	86MM
35-140MM WILCAM	T3.5/16	5'	BNCR	2 lbs	5 1/4"	76MM
50-300MM CANON	T4.5/22	8'	PL-BNCR	4.5 lbs	10 1/4"	102MM
150-600MM CLAIRMONT	T8/45	10'	PL-BNCR-NK	16 lbs	19"	120MM
140-420MM ISCO	T2.7/22	10'6"	PL	42 lbs	27 1/2"	9"

16.5-110MM ARRI MASTER ZOOM	T2.6/22	2'4"	PL	26.4 lbs	17.4"	163MM
--------------------------------	---------	------	----	----------	-------	-------

BREATHING: MINIMAL

RAMPING: T2.8 (16.5mm - 80mm)

T3.2 (80mm - 110mm)

COMMENTS: ALL 1.4X AND 2X EXTENDERS DO NOT WORK.

LENS USE 19mm RODS, LOW BRIDGE AND TOP BALANCE PLATE.

SFF MUST BE USED WITH CUSTOM CCI MADE OFFSET BRKT.

<u>VARIABLE PRIMES</u>	T-STOP	MIN. FOCUS	MOUNTS	WT/LBS	LENGTH	FRONT DIA.
16-30MM VP	T2.2/22	2'	PL	9.5 lbs	6.8"	150MM
29-60MM VP	T2.2/22	2'9"	PL	13.75 lbs	9.6"	150MM
55-105MM VP	T2.2/22	2'9"	PL	12.5 lbs	8.5"	150MM

<u>TELEPHOTO LENSES</u>	T-STOP	MIN. FOCUS	MOUNTS	WT/LBS	LENGTH	FRONT DIA.
200MM CANON	T2/22	10'	PL	7.5 lbs	9"	120MM
200MM NIKKOR	T2/16	9'	PL/BNC/NK	6.5 lbs	8 7/8"	120MM
300MM CANON	T2.8/32	9'9"	PL/BNC/NK	9 lbs	9 1/2"	124MM
300MM NIKKOR	T2/16	13'	PL/BNC/NK	18 lbs	13 1/2"	178MM
300MM ZEISS	T3/32	11'6"	PL/BNC/NK	7 lbs	9 5/8"	120MM
400MM CANON	T2.8/22	12'3"	PL/BNC/NK	12 lbs	13 5/8"	162MM
400MM NIKKOR	T2.8/22	13'2"	PL/BNC/NK	14 lbs	15"	158MM
500MM CANON	T4.5/32	15'3"	PL/BNC/NK	7 lbs	15 1/4"	124MM
500MM NIKKOR	T4/32	15'6"	PL/BNC/NK	10 lbs	15 1/4"	132MM
600MM CANON	T4.5/32	25'	PL/BNC/NK	10 lbs	18"	152MM
600MM NIKKOR	T4/32	25'	PL/BNC/NK	14 lbs	18 1/8"	172MM
800MM CANON	T5.6/32	45'	PL/BNC/NK	10 lbs	22 5/8"	152MM
800MM NIKKOR	T5.6/32	27'	PL/BNC/NK	13 lbs	21 1/4"	158MM
1000MM CLAIRMONT	T4.5/22	60'	PL/BNC/NK	50 lbs	37"	216MM

<u>EXTENDERS</u>					
CENTURY 1.4X EXTENDER	1 STOP LOSS		PL	0.50 lbs	1 1/4"
CENTURY 2X EXTENDER	2 STOP LOSS		PL	1 lbs	2"
ANGENIEUX 1.4X EXT. OPTIMO	1 STOP LOSS		PL	0.50 lbs	1 1/4"
ANGENIEUX 2X EXT. OPTIMO	2 STOP LOSS		PL	0.50 lbs	1 1/4"

<u>ZEISS STD PRIMES</u>	T-STOP	MIN. FOCUS	MOUNTS	WT/LBS	LENGTH	FRONT DIA.
10MM ZEISS	T2.1/22	14"	PL	7.5 lbs	6"	156MM
12MM ARRI	T2.1/22	10"	PL	3 lbs	3 3/4"	135MM
14MM ZEISS MKI	T2/22	2'	PL	4 lbs	4 3/4"	108MM
14MM ZEISS MKII	T2/22	9"	PL	4 lbs	4 1/2"	114MM
16MM ZEISS	T2.1/22	10"	PL	2 lbs	2 1/8"	80MM
20MM ZEISS	T2.1/22	8"	PL	2 lbs	2 1/4"	80MM
24MM ZEISS	T2.1/22	1'2"	PL	1 lbs	2 1/8"	80MM
28MM ZEISS	T2.1/22	11"	PL	2 lbs	3 1/8"	80MM
32MM ZEISS	T2.1/22	2'	PL	1 lbs	2 1/8"	80MM
40MM ZEISS	T2.1/22	1.4"	PL	1 lbs	2 1/4"	80MM
50MM ZEISS	T2.1/22	1'5"	PL	1 lbs	2 1/8"	80MM
85MM ZEISS	T2.1/22	3'	PL	1.5 lbs	2 1/8"	80MM
100MM ZEISS	T2.1/22	3'4"	PL	2 lbs	3"	80MM
135MM ZEISS	T2.1/22	5'	PL	2 lbs	4"	80MM
180MM ZEISS	T3/32	5'	PL	3 lbs	5"	80MM

<u>ZEISS HIGH SPEED PRIMES</u>	T-STOP	MIN. FOCUS	MOUNTS	WT/LBS	LENGTH	FRONT DIA.
18MM ZEISS	T1.3/16	10"	PL	3 lbs	3 3/4"	80MM
25MM ZEISS	T1.3/16	10"	PL	2.5 lbs	2 3/8"	80MM
35MM ZEISS	T1.3/16	14'	PL	2.25 lbs	2 3/8"	80MM
50MM ZEISS	T1.3/16	2'4"	PL	2 lbs	2 3/8"	80MM
65MM ZEISS	T1.3/16	2'4"	PL	2.5 lbs	2 5/8"	80MM
85MM ZEISS	T1.3/16	3'	PL	2.75 lbs	2 3/8"	80MM

<u>ZEISS CLOSE FOCUS</u>	T-STOP	MIN. FOCUS	MOUNTS	WT/LBS	LENGTH	FRONT DIA.
16MM ZEISS C.F.	T2.1/22	6"	PL	2 lbs	2 1/8"	80MM
24MM ZEISS C.F.	T2.1/22	6"	PL	1 lbs	2 1/8"	80MM
32MM ZEISS C.F.	T2.1/22	9"	PL	1 lbs	2 1/8"	80MM
18MM ZEISS C.F.	T1.3/16	9"	PL	3 lbs	3 3/4"	80MM
25MM ZEISS C.F.	T1.3/16	9"	PL	2.5 lbs	2 3/8"	80MM

<u>ZEISS ULTRA PRIMES</u>	T-STOP	MIN. FOCUS	MOUNTS	WT/LBS	LENGTH	FRONT DIA.
8MM U.P. RECTILINEAR	T2.8/22	1'3"	PL	3.5 lbs	5 1/2"	134MM
10MM U.P.	T2.1/22	15"	PL	7.5 lbs	6"	156MM
12MM U.P.	T2/22	15"	PL	5 lbs	5 1/2"	156MM
14MM U.P.	T1.9/22	9"	PL	4.5 lbs	4 1/2"	114MM
16MM U.P.	T1.9/22	12"	PL	4 lbs	4"	95MM
20MM U.P.	T1.9/22	12"	PL	4 lbs	4"	95MM
24MM U.P.	T1.9/22	12"	PL	4 lbs	4"	95MM
28MM U.P.	T1.9/22	12"	PL	4 lbs	4"	95MM
32MM U.P.	T1.9/22	15"	PL	4 lbs	4"	95MM
40MM U.P.	T1.9/22	15"	PL	4 lbs	4"	95MM
50MM U.P.	T1.9/22	2'	PL	3.5 lbs	4"	95MM
65MM U.P.	T1.9/22	2'3"	PL	4 lbs	4"	95MM
85MM U.P.	T1.9/22	3'	PL	4 lbs	4"	95MM
100MM U.P.	T1.9/22	3'3"	PL	4 lbs	4"	95MM
135MM U.P.	T1.9/22	5'	PL	5 lbs	5"	95MM
180MM U.P.	T1.9/22	8'6"	PL	5 lbs	7 1/2"	114MM

<u>ZEISS LDS ULTRA PRIMES</u>	T-STOP	MIN. FOCUS	MOUNTS	WT/LBS	LENGTH	FRONT DIA.
14MM LDS U.P.	T1.9/22	9"	PL	4.5 lbs	5"	114MM
16MM LDS U.P.	T1.9/22	12"	PL	4 lbs	4"	104MM
20MM LDS U.P.	T1.9/22	12"	PL	3.50 lbs	4"	104MM
24MM LDS U.P.	T1.9/22	12"	PL	3.50 lbs	4"	104MM
28MM LDS U.P.	T1.9/22	12"	PL	3.50 lbs	4"	104MM
32MM LDS U.P.	T1.9/22	15"	PL	3.50 lbs	4"	104MM
40MM LDS U.P.	T1.9/22	15"	PL	3 lbs	4"	104MM
50MM LDS U.P.	T1.9/22	2'	PL	3 lbs	4"	104MM
65MM LDS U.P.	T1.9/22	2'3"	PL	3.50 lbs	4"	104MM
85MM LDS U.P.	T1.9/22	3'	PL	3.50 lbs	4"	104MM
100MM LDS U.P.	T1.9/22	3'3"	PL	4 lbs	4"	104MM
135MM LDS U.P.	T1.9/22	5'	PL	5 lbs	5"	104MM

<u>ZEISS MASTER PRIMES</u>	T-STOP	MIN. FOCUS	MOUNTS	WT/LBS	LENGTH	FRONT DIA.
12MM LDS M.P.	T1.3/22	16"	PL	6.4 lbs	9.8"	156MM
14MM LDS M.P.	T1.3/22	14"	PL	5.3 lbs	8.8"	114MM
16MM LDS M.P.	T1.3/22	14"	PL	4.8 lbs	8"	114MM
18MM LDS M.P.	T1.3/22	14"	PL	4.8 lbs	8"	114MM
21MM LDS M.P.	T1.3/22	14"	PL	5.3 lbs	8"	114MM
25MM LDS M.P.	T1.3/22	14"	PL	5.1 lbs	8"	114MM
27MM LDS M.P.	T1.3/22	14"	PL	4.8 lbs	8"	114MM
32MM LDS M.P.	T1.3/22	14"	PL	5.1 lbs	8"	114MM
35MM LDS M.P.	T1.3/22	14"	PL	4.8 lbs	8"	114MM
40MM LDS M.P.	T1.3/22	16"	PL	5.1 lbs	8"	114MM
50MM LDS M.P.	T1.3/22	20"	PL	5.9 lbs	8"	114MM
65MM LDS M.P.	T1.3/22	2'3"	PL	5.7 lbs	8"	114MM
75MM LDS M.P.	T1.3/22	2'9"	PL	6.2 lbs	8"	114MM
100MM LDS M.P.	T1.3/22	3'6"	PL	6.4 lbs	8"	114MM
150MM LDS M.P.	T1.3/22	4'11"	PL	8.8 lbs	10.3"	134MM

<u>MACRO LENSES</u>	T-STOP	MIN. FOCUS	MOUNT	WT/LBS	LENGTH	FRONT DIA.
16MM	T2.1/22	5.5"	PL	2.5 lbs	3 1/4"	80MM
24MM	T2.1/22	6.5"	PL	2.5 lbs	3 1/4"	80MM
32MM	T2.1/22	7.5"	PL	2 lbs	3 1/4"	80MM
40MM	T2.1/22	9"	PL	2 lbs	3 1/4"	80MM
50MM	T3/64	7.5"	PL	3.5 lbs	4 1/2"	80MM
60MM MACRO	T3/32	11"	PL	2 lbs	3 1/2"	80MM
100MM	T3/64	13.5"	PL	4 lbs	6 1/2"	80MM
105MM NIKKOR	T2.8/32	1'4"	NK	1 lbs	3 1/4"	52MM
152MM COOKE MACRO	T3.2/22	2'3"	PL/BNCR	5.5 lbs	10 5/8"	85.75MM
200MM NIKKOR MACRO	T4/32	2'4"	PL/NK/BNCR	2 lbs	7"	52MM

<u>LONG DIST. MACRO</u>	T-STOP	TAKING DIST.	MOUNT	WT/LBS	LENGTH	FRONT
OBJ. 10X-7.8X MAGNIFICATION	T22/64	1.9"-2.3"	PL/NK/BNC	5 lbs	18"	29.50MM
OBJ. 5.3X-3.9X MAGNIFICATION	T22/64	3.9"-5.1"	PL/NK/BNC	5 lbs	18"	58MM
OBJ. 3.9X-2.4X MAGNIFICATION	T22/64	5.9"-8.7"	PL/NK/BNC	5 lbs	17"	58MM
OBJ. 2.1X-0.8X MAGNIFICATION	T22/64	12"-28"	PL/NK/BNC	5 lbs	17 3/4"	58MM
OBJ. 1.6X-0.3X MAGNIFICATION	T22/64	16"-79"	PL/NK/BNC	5 lbs	17 1/2"	58MM

<u>COOKE S4/i LENSES</u>	T-STOP	MIN. FOCUS	MOUNTS	WT/LBS	LENGTH	FRONT DIA.
12MM	T2/22	9"	PL	6.5 lbs	5"	156MM
14MM	T2/22	9"	PL	4.8 lbs	5"	110MM
16MM	T2/22	9"	PL	5.4 lbs	5"	110MM
18MM	T2/22	9"	PL	3.85 lbs	4.5"	110MM
21MM	T2/22	9"	PL	4.4 lbs	4.5"	110MM
25MM	T2/22	9"	PL	3.5 lbs	4.5"	110MM
27MM	T2/22	10"	PL	3.55 lbs	4.5"	110MM
32MM	T2/22	12"	PL	4 lbs	5"	110MM
35MM	T2/22	14"	PL	4.2 lbs	5"	110MM
40MM	T2/22	16"	PL	4.4 lbs	5.5"	110MM
50MM	T2/22	20"	PL	3.3 lbs	4.9"	110MM
65MM	T2/22	27"	PL	3.55 lbs	4.9"	110MM
75MM	T2/22	30"	PL	3.85 lbs	4.9"	110MM
100MM	T2/22	36"	PL	4.4 lbs	5.5"	110MM
135MM	T2/22	30"	PL	4.95 lbs	7.3"	110MM
150MM	T2/22	42"	PL	7.7 lbs	6.2"	125MM
180MM	T2/22	51"	PL	9.45 lbs	7.3"	136MM

<u>COOKE 5i LENSES</u>	T-STOP	MIN. FOCUS	MOUNTS	WT/LBS	LENGTH	FRONT DIA.
18MM	T1.4/22	14"	PL	TBD	6.85"	110MM
25MM	T1.4/22	14"	PL	TBD	4.61"	110MM
32MM	T1.4/22	14"	PL	TBD	4.61"	110MM
40MM	T1.4/22	16"	PL	TBD	4.61"	110MM
50MM	T1.4/22	20"	PL	TBD	4.61"	110MM
65MM	T1.4/22	24"	PL	TBD	4.61"	110MM
75MM	T1.4/22	27"	PL	TBD	4.61"	110MM
100MM	T1.4/22	30"	PL	TBD	7.20"	110MM
135MM	T1.4/22	TBD	PL	TBD	TBD	TBD

<u>EYEMO/NIKKOR LENSES</u>	T-STOP	MIN. FOCUS	MOUNTS	WT/LBS	LENGTH	FRONT DIA.
8MM (FISH EYE)	T2.8/22	9"	NIKON	3.5 lbs	6"	120.5MM
14MM	T2.8/22	8"	NIKON	1.5 lbs	3 1/2"	87MM
15MM	T3.5/22	12"	NIKON	1.25 lbs	3 1/4"	89MM
18MM	T2.8/22	10"	NIKON	1 lbs	2 3/8"	80MM
18MM	T3.5/22	10"	NIKON	1 lbs	2 1/2"	76MM
20MM	T2.8/22	10"	NIKON	0.50 lbs	1 5/8"	63.5MM
24MM	T2/22	12"	NIKON	0.50 lbs	2 1/8"	54MM
28MM	T1.4/16	15"	NIKON	1.25 lbs	3 1/8"	76MM
28MM	T2/22	11"	NIKON	1 lbs	2 3/8"	54MM
35MM	T1.4/16	12"	NIKON	1 lbs	2 1/2"	54MM
35MM	T2/22	12"	NIKON	0.50 lbs	2 1/8"	54MM
50MM	T1.2/16	21"	NIKON	1 lbs	2"	54MM
50MM	T1.4/16	18"	NIKON	0.50 lbs	1 3/4"	54MM
50MM	T1.8/22	24"	NIKON	0.25 lbs	1 1/4"	54MM
55MM	T2.8/32	10"	NIKON	0.50 lbs	2 1/2"	54MM
105MM	T2.8/32	15"	NIKON	1 lbs	3 1/4"	57MM

<u>COOKE CF PANCHROS</u>	T-STOP	MIN. FOCUS	MOUNTS	WT/LBS	LENGTH	FRONT DIA.
18MM	T2.2/22	5.5"	PL	1.25 lbs	2"	80MM
25MM	T2.2/22	5.5"	PL	1.25 lbs	2"	80MM
32MM	T2.3/22	6.5"	PL	1 lbs	2 1/8"	80MM
40MM	T2.3/22	7"	PL	1.5 lbs	2 5/8"	80MM
50MM	T2.3/22	8"	PL	2 lbs	3 1/4"	80MM
75MM	T2.3/22	1'3"	PL	2 lbs	3 1/4"	80MM
100MM	T2.8/22	1'5"	PL	3 lbs	4 1/4"	80MM

<u>COOKE PANCHROS</u>	T-STOP	MIN. FOCUS	MOUNT	WT/LBS	LENGTH	FRONT DIA.
18MM	T2.2/22	12"	PL	1.25 lbs	1 7/8"	80MM
25MM	T2.2/22	12"	PL	1 lbs	2 1/8"	80MM
32MM	T2.3/22	12"	PL	1 lbs	2 1/2"	80MM
40MM	T2.3/22	12"	PL	1 lbs	2 5/8"	80MM
50MM	T2.3/22	1'6"	PL	1 lbs	2 5/8"	80MM
75MM	T2.3/22	2'	PL	2 lbs	3"	80MM
100MM	T2.8/22	3'	PL	2.5 lbs	4 3/8"	80MM

<u>SWING AND TILT LENSES</u>	T-STOP	MOUNT	WT/LBS	LENGTH	FRONT DIA.
14MM CENTURY (CANON)	T2.8/22	S&T MOUNT	1.50 lbs	3 3/4"	85MM
18MM NIKKOR	T3.8/22	S&T MOUNT	1.50 lbs	3 1/4"	93MM
20MM NIKKOR	3.2/22	S&T MOUNT	1.50 lbs	3 1/4"	93MM
20MM CENTURY	3.2/22	S&T MOUNT	1.50 lbs	3 1/4"	85MM
24MM OLYMPUS	T3.8/22	S&T MOUNT	1..50 lbs	3"	84MM
28MM PENTAX	T3.8/22	S&T MOUNT	2 lbs	3"	84MM
35MM CANON	T3.2/22	S&T MOUNT	1.50 lbs	3 1/2"	84MM
50MM ZEISS	T4/32	S&T MOUNT	2 lbs	3 3/4"	84MM
60MM ZEISS	T3.5/22	S&T MOUNT	2 lbs	3 1/4"	84MM
80MM ZEISS	T2.8/22	S&T MOUNT	1.50 lbs	2 1/2"	84MM
105MM CENTURY	T2.4/16	S&T MOUNT	1..50 lbs	3 3/4"	85MM
110MM ZEISS	T2.4/22	S&T MOUNT	2 lbs	3 1/2"	84MM
120MM ZEISS (MACRO)	T4/32	PL	5 lbs	5"	84MM
135MM ZEISS (MACRO)	T5.6/45	PL	5 lbs	5"	84MM
150MM ZEISS	T2.8/16	S&T MOUNT	2 lbs	3 3/4"	84MM

<u>OPTEX/NIKKOR C.F.</u>	T-STOP	MIN. FOCUS	MOUNTS	WT/LBS	LENGTH	FRONT DIA.
15MM	T3.5/32	7"	PL-BNCR	2 lbs	3 1/4"	100MM
20MM	T2.8/22	6"	PL-BNCR	1.5 lbs	2 1/2"	89MM
24MM	2.8/22	6"	PL-BNCR	1.5 lbs	2 3/4"	89MM
28 MM	T2.8/22	6.5"	PL-BNCR	1.5 lbs	3"	89MM
35MM	T2.8/22	8"	PL-BNCR	1.5 lbs	3"	89MM

<u>WIDE ANGLE LENSES</u>	T-STOP	MIN. FOCUS	MOUNTS	WT/LBS	LENGTH	FRONT DIA.
6MM NIKKOR (FISH EYE) 220° ANGLE OF VIEW	T2.8/22	12"	PL	14 lbs	8 1/2"	238MM
7.5MM CENTURY (FISH EYE)	T5/22	3'	PL	1 lbs	2 3/4"	80MM
8MM NIKKOR (FISH EYE)	T2.8/22	9"	PL	3.5 lbs	6"	120.5MM
8MM U.P. RECTILINEAR	T2.8/22	1'3"	PL	3.5 lbs	5 1/2"	134MM
9.8MM KINOPTIC	T2.3/22	8.5"	PL	4.25 lbs	5 1/4"	89MM
10.5MM OPTEX	T2.1/22	6"	PL	2.25 lbs	3 1/2"	120.5MM
12MM TECHNO	T2.1/22	8"	PL	4 lbs	4"	155.5MM

<u>ARRI SLANT FOCUS LENSES</u>	T-STOP	MIN. FOCUS	MOUNTS	WT/LBS	LENGTH	FRONT DIA.
24MM	T4	13"	PL	2 lbs	4"	87MM
45MM	T2.8	15"	PL	2.5 lbs	4.5"	87MM
90MM	T2.8/22	20"	PL	3 lbs	5 1/4"	87MM

<u>BLURTAR LENSES</u>	T-STOP	MIN. FOCUS	MOUNTS	WT/LBS	LENGTH	FRONT DIA.
28MM BLURTAR	T2.3/16	2'	PL	1 lbs	2 1/2"	80MM
40MM BLURTAR	T2.6/16	2'	PL	1lbs	2 1/2"	80MM
50MM BLURTAR	T3/16	2'	PL	1 lbs	2 1/2"	80MM
75MM BLURTAR	T3.8/22	5'	PL	1 lbs	3 1/2"	80MM

ANAMORPHIC LENSES

ANAMORPHIC ZOOM LENSES

	T-STOP	MIN. FOCUS	MOUNTS	WT/LBS	LENGTH	FRONT DIA.
28-140MM COOKE	T4.5/32	2'4"	PL/BNCR	17 lbs	15 3/4"	197MM
34-204MM ANGENIEUX	T4.5/32	2'6"	PL/BNCR	20 lbs	16 1/4"	155MM
36-200MM COOKE	T4.5/32	2'4"	PL/BNCR	13 lbs	13 1/2"	149MM
40-120MM COOKE	T4.5/32	2'4"	PL/BNCR	12.5 lbs	9 3/4"	120MM
40-200MM COOKE	T4.5/32	2'4"	PL/BNCR	7.5 lbs	13 1/2"	142MM
50-500MM COOKE MKII	T5.6/32	5'6"	PL/BNCR	12.5 lbs	12 5/8"	120MM
50-500MM COOKE MKIII	T5.6/32	5'6"	PL/BNCR	19 lbs	15"	152MM
50-500MM ANG. HR	T5.6/32	5'7"	PL/BNCR	11.5 lbs	12 3/4"	133MM
300-1200MM CCI	T11/64	10'	PL/BNCR	17 lbs	19"	120MM

ANAMORPHIC PRIME LENSES

HAWK LENSES

	T-STOP	MIN. FOCUS	MOUNTS	WT/LBS	LENGTH	FRONT DIA.
25MM HAWK V-SERIES	T2.2/16	3'6"	PL	6 lbs	5"	142MM
30MM HAWK C-SERIES	T2.2/16	3'6"	PL	11 lbs	6 3/4"	142MM
35MM HAWK V-SERIES	T2.2/16	2'6"	PL	12.3 lbs	7.4"	156MM
40MM HAWK C-SERIES	T2.2/16	3'6"	PL	4.8 lbs	5 1/2"	110MM
50MM HAWK C-SERIES	T2.2/16	3'6"	PL	4.6 lbs	6"	110MM
50MM HAWK V-SERIES	T2.2/16	2'	PL	8.1 lbs	8"	125MM
60MM HAWK C-SERIES	T2.2/16	3'6"	PL	4.6 lbs	7"	110MM
60MM HAWK V-SERIES	T2.2/16	2'	PL	8.8 lbs	8.4"	125MM
75MM HAWK C-SERIES	T2.2/16	3'6"	PL	5.2 lbs	7 1/2"	110MM
100MM HAWK C-SERIES	T3/16	3'6"	PL	5.9 lbs	8 1/2"	110MM
100MM HAWK V-SERIES	T2.2/16	3'6"	PL	14.5 lbs	12.8"	125MM
135MM HAWK C-SERIES	T3/16	3'6"	PL	12 lbs	12"	110MM
135MM HAWK V-SERIES	T3/22	3'6"	PL	13.8 lbs	12.8"	125MM
180MM HAWK V-SERIES	T3/22	6'6"	PL	16.5 lbs	16"	142MM
250MM HAWK V-SERIES	T3/16	6'6"	PL	18 lbs	17 3/4"	142MM

CCI ANAMORPHICS

	T-STOP	MIN. FOCUS	MOUNT	WT/LBS	LENGTH	FRONT DIA.
32MM CLAIRMONT	T2.3/22	2'6"	PL	5 lbs	6 1/8"	130MM
40MM CLAIRMONT	T2.3/22	3'	PL	3 lbs	4 1/8"	80MM
50MM CLAIRMONT	T2.3/22	3'	PL	3 lbs	4 1/2"	80MM
75MM CLAIRMONT	T2.8/22	3'	PL	4 lbs	5 3/8"	80MM
100MM CLAIRMONT	T3.4/22	5'	PL	4.5 lbs	7"	80MM

<u>TODD AO ANAMORPHICS</u>	T-STOP	MIN. FOCUS	MOUNTS	WT/LBS	LENGTH	FRONT DIA.
28MM TODD AO	T3.9/22	5'	PL	3 lbs	2 7/8"	124MM
35MM TODD AO	T1.4/16	2'6"	PL/BNCR	8 lbs	7 3/8"	130MM
38MM TODD AO	T2.3/22	3'	PL	5 lbs	5"	124MM
55MM TODD AO	T1.4/22	1'6"	PL/BNCR	4.5 lbs	6 1/2"	95MM
75MM TODD AO	T2.5/22	3'	PL/BNCR	5 lbs	6 3/8"	98.5 MM
100MM TODD AO	T3.4/32	3'	PL/BNCR	6 lbs	8 1/4"	98MM
200MM TODD AO macro	T4/32	1'6"	PL/BNCR	4 lbs	6 5/8"	80MM

<u>NIKKOR TELE-ANAMORPHICS</u>	T-STOP	MIN. FOCUS	MOUNTS	WT/LBS	LENGTH	FRONT DIA.
400MM NIKKOR	T4/22	9'	PL/BNCR	7.5 lbs	8 7/8"	120MM
400MM NIKKOR macro	T6/32	1'7"	PL/BNCR	3 lbs	7"	67MM
600MM NIKKOR	T4/32	13'	PL/BNCR	19 lbs	13 1/2"	178MM
800MM NIKKOR	T5.6/32	13'2"	PL/BNCR	15 lbs	15"	158MM
1000MM NIKKOR	T6.8/32	15'6"	PL/BNCR	11 lbs	15 1/4"	133MM
1200MM NIKKOR	T6.3/32	25'	PL/BNCR	15 lbs	18 1/8"	172MM
1600MM NIKKOR	T9/32	27'	PL/BNCR	14 lbs	21 1/4"	158MM

<u>CANON TELE-ANAMORPHICS</u>	T-STOP	MIN. FOCUS	MOUNTS	WT/LBS	LENGTH	FRONT DIA.
600MM CANON	T4.5/32	9'9"	PL/BNCR	10 lbs	9 1/2"	124MM
800MM CANON	T5.6/32	12'3"	PL/BNCR	13 lbs	13 5/8"	162MM
1000MM CANON	T8/32	15'6"	PL/BNCR	8 lbs	15 1/4"	124MM
1200MM CANON	T6.3/32	25'	PL/BNCR	11 lbs	18"	152MM
1600MM CANON	T9/32	45'	PL/BNCR	11 lbs	22 5/8"	152MM
300-1200MM CANON	T11/64	9'9"	PL/BNCR	11 lbs	19"	120MM
2000MM CCI ANAMOR.	T8/32	60'	PL/BNCR	51 lbs	37"	216MM

16MM FORMAT LENSES

<u>SUPER 16MM ZOOM LENSES</u>	T-STOP	MIN. FOCUS	MOUNT	WT/LBS	LENGTH	FRONT DIA.
6.6-66MM CANON	T2.7/16	24"	PL	4.7 lbs	7 3/4"	110MM
7-81MM ANGENIEUX	T2.4/22	2'	PL	5 lbs	9 1/2"	100MM
7-63MM CANON	T2.6/22	2'	PL	5 lbs	9"	95MM
8-64MM CANON	T2.4/22	1'10"	PL	5 lbs	7 7/8"	95MM
10.6-180MM CANON	T2.7/16	40"	PL	3.6 lbs	9"	95MM
11-110MM ZEISS	T2.2/16	5'	PL/B	4.5 lbs	6"	87MM
11.5-138MM ANGENIEUX	T2.3/22	5'	PL	7 lbs	7 3/4"	114MM
11-165MM CANON	T2.5-2.8/22	3'5"	PL	5 lbs	7 1/2"	95MM
15-300MM ANGENIEUX	T5/22	5'	PL	5.5 lbs	8 3/4"	98.5MM
<u>STD16MM ZOOM LENSES</u>	T-STOP	MIN. FOCUS	MOUNT	WT/LBS	LENGTH	FRONT DIA.
9-50MM COOKE	T2.5/22	1'6"	PL/B	4 lbs	6 3/4"	83MM
9.5-57MM ANG.	T1.9-2.8/22	2'	PL/B	2.5 lbs	5 3/4"	67MM
10-30MM COOKE	T1.6/16	2'4"	PL	6.5 lbs	8"	121MM
10-100MM ZEISS	T2/16	5'	PL/B	4.5 lbs	6"	87MM
CENTURY 2X EXTENDER	2 STOP LOSS		PL			

<u>SUPER 16MM PRIME LENSES</u>	T-STOP	MIN. FOCUS	MOUNTS	WT/LBS	LENGTH	FRONT DIA.
4.5MM ELITE	T2.2/22	6"	PL	1.50 lbs	2.5"	70MM
6MM CENTURY	T1.9/16	12"	PL	3 lbs	5 1/2"	85.75MM
7MM OPTAR	T1.3/16	8"	PL	3.5 lbs	3"	104MM
8MM OPTAR	T1.3/16	10"	PL	2 lbs	2 1/4"	80MM
20MM ELITE	T1.3/22	10"	PL	2 lbs	2 3/4"	80MM
35MM PANTHER	T1.3/16	24"	PL	2 lbs	4"	80MM
9.5MM ZEISS	T1.3/16	10"	PL	1.5 lbs	2 1/2"	80MM
12MM ZEISS	T1.3/16	8"	PL	1.5 lbs	2 1/2"	80MM
16MM ZEISS	T1.3/16	10"	PL	1.5 lbs	2 1/2"	80MM
25MM ZEISS	T1.3/16	10"	PL	2 lbs	2 3/4"	80MM
50MM ZEISS	T1.3/16	2'4"	PL	2 lbs	2 3/4"	80MM
6MM ARRI ULTRA 16	T1.3/16	8"	PL	2.2 lbs	3.6"	95MM
8MM ARRI ULTRA 16	T1.3/16	12"	PL	2.2 lbs	3.6"	95MM
9.5MM ARRI ULTRA 16	T1.3/16	12"	PL	2.2 lbs	3.6"	95MM
12MM ARRI ULTRA 16	T1.3/16	12"	PL	2.2 lbs	3.6"	95MM
14MM ARRI ULTRA 16	T1.3/16	12"	PL	2.2 lbs	3.6"	95MM
18MM ARRI ULTRA 16	T1.3/16	12"	PL	2.6 lbs	3.6"	95MM
25MM ARRI ULTRA 16	T1.3/16	12"	PL	2.6 lbs	3.6"	95MM
35MM ARRI ULTRA 16	T1.3/16	14"	PL	2.4 lbs	3.6"	95MM
50MM ARRI ULTRA 16	T1.3/16	14"	PL	2.6 lbs	3.6"	95MM
6MM SK4 COOKE	T2/22	8"	PL	3.5lbs	6.5"	110MM
9.5MM SK4 COOKE	T2/22	8"	PL	3.5lbs	6.5"	110MM
12MM SK4 COOKE	T2/22	8"	PL	3.5lbs	6.5"	110MM
<u>STD 16MM PRIME LENSES</u>	T-STOP	MIN. FOCUS	MOUNTS	WT/LBS	LENGTH	FRONT DIA.
4MM OPTEX	T2/22	FIXED	PL/B	3 lbs	3"	152.5MM
5.9MM ANGENIEUX	T2/22	FIXED	PL/B/C	1 lbs	1 5/8"	75MM
8MM ZEISS	T2.1/22	8"	PL	1 lbs	2"	80MM
<u>C-MOUNT LENSES</u>	T-STOP	MIN. FOCUS	MOUNTS	WT/LBS	LENGTH	FRONT DIA.
5.9MM ANGENIEUX	T2/22	5'/FIXED	PL/B/C	1 lbs	1 5/8"	75MM
10MM	F1.8/16	5'/FIXED	C-MOUNT	.50 lbs	2"	42mm
15MM	F1.3/16	10"	C-MOUNT	.50 lbs	2 1/2"	42mm
25MM	F1.4/22	18"	C-MOUNT	.50 lbs	1 3/4"	42mm
50MM	F1.8/22	3'	C-MOUNT	.50 lbs	2"	42mm

HIGH DEFINITION LENSES

<u>FUJINON C-SERIES PRIMES</u>	T-STOP	MIN. FOCUS	MOUNT	WT/LBS	LENGTH	FRONT DIA.
5MM FUJINON C	T2/16	20"	B4	5 lbs	8"	120MM
8MM FUJINON C	T1.5/16	20"	B4	3 lbs	6"	95MM
12MM FUJINON C	T1.5/16	16.5"	B4	2.5 lbs	5.5"	95MM
16MM FUJINON C	T1.5/16	16.5"	B4	2.5 lbs	5.5"	95MM
20MM FUJINON C	T1.5/16	18"	B4	2.5 lbs	5.5"	95MM
34MM FUJINON C	T1.5/16	16"	B4	2.5 lbs	5.5"	95MM
40MM FUJINON C	T1.5/16	20"	B4	2.5 lbs	5.5"	95MM
54MM FUJINON C	T1.6/16	23.5"	B4	2.5 lbs	5.5"	95MM
<u>FUJINON E-SERIES PRIMES</u>	T-STOP	MIN. FOCUS	MOUNTS	WT/LBS	LENGTH	FRONT DIA.
5MM FUJINON E	T1.7/16	20"	B4	4.8 lbs	7 1/8"	95MM
8MM FUJINON E	T1.5/16	16"	B4	3.5 lbs	5.75"	95MM
10MM FUJINON E	T1.5/16	20"	B4	3.5 lbs	5.75"	95MM
12MM FUJINON E	T1.5/16	16"	B4	3.5 lbs	5.75"	95MM
16MM FUJINON E	T1.5/16	16"	B4	3.5 lbs	5.75"	95MM
20MM FUJINON E	T1.5/16	18"	B4	3.5 lbs	5.75"	95MM
34MM FUJINON E	T1.5/16	16"	B4	3.5 lbs	5.75"	95MM
40MM FUJINON E	T1.5/16	20"	B4	3.5 lbs	5.75"	95MM
54MM FUJINON E	T1.6/16	24"	B4	3.5 lbs	5.75"	95MM

<u>ZEISS DIGI-PRIMES</u>	T-STOP	MIN. FOCUS	MOUNT	WT/LBS	LENGTH	FRONT DIA.
3.9MM ZEISS	T1.9/16	20"	B4	4.5 lbs	9"	117MM
5MM ZEISS	T1.9/16	20"	B4	3.5 lbs	6.5"	95MM
7MM ZEISS	T1.6/16	20"	B4	3.5 lbs	6.5"	95MM
10MM ZEISS	T1.6/16	20"	B4	3.5 lbs	6.5"	95MM
14MM ZEISS	T1.6/16	20"	B4	3 lbs	6.5"	95MM
20MM ZEISS	T1.6/16	20"	B4	3 lbs	6.5"	95MM
28MM ZEISS	T1.6/16	20"	B4	3 lbs	7.25"	95MM
40MM ZEISS	T1.6/16	20"	B4	3.5 lbs	6.5"	95MM
70MM ZEISS close focus	T1.6/16	13"	B4	4 lbs	8.5"	95MM

<u>ZEISS DIGI-ZOOMS</u>	T-STOP	MIN. FOCUS	MOUNT	WT/LBS	LENGTH	FRONT DIA.
6-24MM ZEISS	T1.9/16	22"	B4	6.1 lbs	9.8"	95MM
17-112MM ZEISS	T1.9/16	30"	B4	9 lbs	11.8"	95MM

<u>CANON HD ZOOMS</u>	T-STOP	MIN. FOCUS	MOUNTS	WT/LBS	LENGTH	FRONT DIA.
4.7-52MM CANON	T2.1/16	23"	B4	3.5 lbs	9.5"	95MM
4.7-52MM CANON ENG	T1.9/16	23"	B4	4 lbs	9.5"	95MM
7.5-158MM CANON	T2.1/16	45"	B4	5.25 lbs	10.25"	130MM
7.7-131MM CANON ENG	T1.8/16	30"	B4	4.5 lbs	8.75"	98MM

<u>FUJINON HD ZOOMS</u>	T-STOP	MIN. FOCUS	MOUNTS	WT/LBS	LENGTH	FRONT DIA.
4.5-59MM FUJINON	T2/16	2'	B4	4.5 lbs	10 1/8"	95MM
5-50MM FUJINON	T2.4/16	34"	B4	4 lbs	9 1/4"	95MM
7.3-110MM FUJINON	T2/16	48"	B4	6.5 lbs	12"	110MM
10-100MM FUJINON	T1.8/16	36"	B4	12.75 lbs	12.5"	128MM
6-30MM FUJINON	T1.8/16	23"	B4	11.5 lbs	11"	128MM

<u>P&S TECHNICH ADAPTORS</u>	WT/LBS	LENGTH
PRO35 B4 TO PL	4 lbs	6 3/4"
HVX200 MINI35 ADAPT.	7.50 lbs	15"

<u>HD ACCESORIES</u>	
FUJINON 1.4 EXT	1 STOP LOSS
OPTEX 2X EXT.	2 STOP LOSS
CENTURY 2X EXT.	2 STOP LOSS
CENTURY COLOR CORRECTOR FOR TELEPHOTOS	
CENTURY HD COLLIMATOR	

REVOLUTION SYSTEM

T-STOP	MIN. FOCUS	WT/LBS	LENGTH
--------	------------	--------	--------

CONFIGURATIONS:

REVOLUTION + PL SWIVEL	T7.5/45	VARIES	14 lbs+ PRIME	23 1/2" + PRIME
REVOLUTION + MINI-PL SWIVEL	T7.5/45	VARIES	12 lbs	18 1/2" + MINI-PL LENS
REVOLUTION + PL HORIZON TRACKER	T7.5/45	VARIES	11 lbs+PRIME	28 3/4"
REVOLUTION + MINI-PL HORIZON TRACKER	T7.5/45	VARIES	10.50 lbs	23 1/2"
REVOLUTION + PL BORESCOPE	T7.5/45	VARIES	11 lbs+PRIME	25"+PRIME LENS
REVOLUTION + MINI-PL BORESCOPE	T7.5/45	VARIES	10 lbs	21 3/4" + MINI-PL LENS

ACCESSORIES: NIKON TILT FOCUS ATTACHMENT, LEICA ADAPTOR, MODULE AXIX LOCK

MINI-PL LENSES	LENGTH	WT/LBS
9.8MM	2"	0.50 lbs
12MM	1 3/4"	0.50 lbs
16MM	2"	0.50 lbs
20MM	3"	0.50 lbs
24MM	2 1/4"	0.50 lbs
32MM	2"	0.50 lbs
40MM	2"	0.50 lbs
60MM	2"	0.50 lbs

SKATER SCOPE

T-STOP	MIN. FOCUS	MOUNT	WT/LBS	LENGTH
T5.6		PL / B4	7.3lbs+LENS	13.2"+LENS

T-REX SYSTEM	T-STOP	MIN. FOCUS	MOUNT	WT/LBS	LENGTH	FRONT DIA.
T-REX SYSTEM WITH RIGHT ANGLE ATTACHMENT	T7.1	SEE BELOW	PL	21 lbs+LENS	28 1/2"+LENS	

T-REX LENSES:

5.5-20MM		LENS FRONT		1 lbs	2 1/4"	68MM
8-18MM		LENS FRONT		1 lbs	4"	84MM
17-36MM		LENS FRONT		1 lbs	4"	75MM
32-70MM		4"		0.50 lbs	2 1/2"	63MM

OPTIONAL T-REX SYSTEM

T-REX SYSTEM WITH
STRAIGHT BORESCOPE

T-STOP	MIN. FOCUS	MOUNT	WT/LBS	LENGTH
T5.6	SEE BELOW	PL	16 lbs+LENS	33 1/4"+LENS

OPTIONAL T-REX LENSES:

55-112MM macro		9"		2 lbs	3 1/4"	75MM
20-44MM adj. ball lens		LENS FRONT		1 lbs	4"	80MM
18-35MM slant focus		0.35"		1.50 lbs	4"	75MM

PRAXIS PURE REACH 35" T5
PERISCOPE RELAY SYSTEM

T-STOP	MIN. FOCUS	MOUNT	WT/LBS	LENGTH	FRONT DIA.
T5 (no stop loss)	Dependent on the taking lens	PL	15 lbs	35"	4" at 90° knuckle 3 1/2" the tube

BREATHING AND RAMPING: Dependent on the taking lens.

COMMENTS: Periscope is PL mount only at both ends.
Focus and Iris functions are performed by the taking lens.
Periscope works in both 90° and strait probe mode.
The periscope does not have Focus, Iris or Zoom functions.

OPTICS FOR SPECIAL APPLICATIONS

	T-STOP	WT/LBS	LENGTH
LOW ANGLE PRISM	1/2 STOP LOSS	14 lbs	7"
SPY EFX LENS	TAKING LENS	1.50 lbs	5 1/2" + PRIME LENS
MICROSCOPE LENS magnification: 4X/10X/40X	T51/54/60	9.50 lbs	13 1/2"
MESMERIZER	TAKING LENS	5 lbs	5"
ZOOM MESMERIZER	1 1/3 STOP LOSS	1 lbs	1 1/4"
RIFLE SCOPE	N/A	4 lbs	12"
NIKON BELLOWS	TAKING LENS	2.50 lbs	9 1/2"
PINHOLE LENSES f48/54.3/68/84/93/114/133/143		0.25 lbs	1"
135MM HASSEIBSLAD BELLOWS			
PEEPHOLE LENS	N/A	3 lbs	2 1/2"
DAREDEVIL DISTORTION LENSES			
KALEIDOSCOPE	T2.8/16	3.50 lbs	10" + PRIME LENS
EXTENTION TUBES:25mm/50mm			

v3 MOE LENSES

	T-STOP	MIN. FOCUS	MOUNTS	WT/LBS	LENGTH
24MM	T2.3	2'	PL	5.5 lbs	3 3/4"
35MM	T1.6	2'3"	PL	5.5 lbs	3 3/4"
50MM	T1.4	2'3"	PL	5.5 lbs	3 3/4"
85MM	T2.1	2'6"	PL	5.5 lbs	3 3/4"
135MM	T2.8	4'3"	PL	5.7 lbs	4 1/4"

WIDE ANGLE ADAPTORS

ASPHERE 16MM FORMAT:

9.5MM=5.6MM, 12MM=6.6MM

6MM CENTURY DOUBLE ASPHERE ATTACHMENT:

6MM=4.5MM

DOUBLE ASPHERE 35MM FORMAT:

16MM=12MM, 18MM=13.5MM

DOUBLE ASPHERE 16MM FORMAT:

8MM=6MM, 9.5MM=7MM, 12MM=9MM

FISH EYE ADAPTOR 16MM FORMAT:

8MM=5MM, 9.5MM=6MM, 12M=7MM

FISH EYE ADAPTOR 35MM FORMAT:

16MM CF=10.5MM (TV SAFE ONLY), 18MM=11.5MM

CENTURY SUPER .7X WIDE ANGLE ATTACHMENT

PERISCOPE/BORESCOPE LENSES

	T-STOP	MIN. FOCUS	MOUNTS	WT/LBS	LENGTH	
INNOVISION PROBE 2+	T6.3/32	SEE BELOW	PL/BNCR/NK	5 lbs+LENS	20'+LENS	
PROBE2+ WITH 90o RIGHT ANGLE	T6.3/32	SEE BELOW	PL/BNCR/NK	4.5 lbs+LENS	17 1/4"+LENS	
PROBE2+ WITH LOW ANGLE PRISM	T6.3/32 1/3 stop loss	SEE BELOW	PL/BNCR/NK	6 lbs	25"	
			LENGHT	FRONT DIA.		
LENSES: 9MM			1/4"	46MM		
12MM			1/2"	46MM		
16MM			1 1/4"	44MM		
20MM			2"	44MM		
32MM			5"	44MM		
40MM			11"	44MM		
CLOSE FOCUS SHIMS	16MM	20MM	32MM			
10	7/8"	1 3/8"	4"			
20	3/4"	1 1/4"	3 3/4"			
30	5/8"	1"	3 1/4"			
40	1/2"	3/4"	3"			
50	3/8"	1/2"	2 1/2"			
75	1/4"	1/4"	1 3/4"			
100	1/8"	1/8"	1 1/2"			
INNOVISION PROBE 1	T16/64		PL/BNCR/B4	2 .50 lbs	20 1/2"	
LENSES: 10, 14, 16, 24, 32, 50MM						
BABY PERISCOPE	T5.6	VARIES	PL/BNCR	4.50 lbs	8" + Prime	VARIES
CENTURY CP2000	T4/22	VARIES	PL/BNCR/B4	11.50 lbs	21 1/4"	VARIES
CENTURY CP2000 WITH STRAIGHT RELAY	T4/22	VARIES	PL/BNCR/B4	12 lbs	22 1/2" + PRIME LENS	VARIES

MASTER DIOPTERS

FOCAL LENGTH	DIOPTER TYPE	M.O.D. FRONT OF LENS
18MM	NO DIOPTER	5 1/2"
	0.5	4 1/2"
	1	4 1/2"
	2	3 3/4"
25MM	NO DIOPTER	5 1/2"
	0.5	5"
	1	4 1/2"
	2	4"
35MM	NO DIOPTER	5 1/2"
	0.5	4 1/2"
	1	4 1/2"
	2	4"
50MM	NO DIOPTER	11"
	0.5	9 1/4"
	1	8 1/4"
	2	7"
75MM	NO DIOPTER	22 1/2"
	0.5	17"
	1	14 1/2"
	2	10 1/2"
100MM	NO DIOPTER	30 1/2"
	0.5	21 1/2"
	1	17"
	2	11 1/2"

DIRECTORS FINDERS

35MM DIRECTOR FINDERS

KISH

CCI

ARRIFLEX -OLD STYLE

ARRIFLEX-NEW STYLE

FRIES

ISCO COMPACT FINDER

BIRNS & SAWYER

35MM ANAMORPHIC FINDERS

KISH

ARRIFLEX -OLD STYLE

16MM FINDERS

KISH

ISCO COMPACT FINDER

BIRNS & SAWYER

FINDERS WITH VIDEO ASSIST

KISH

FRIES